



**TRIPLEX GRIS**  
**COATED WHITE LINED CHIPBOARD**  
**(WLC) WITH GREY BACK**  
**GD 2**

**TECHNICAL SPECIFICATION**

**SEPTEMBER 2020**

SUBSTANCE	CALIPER	BULK	STIFFNESS TABER *(15°)		STIFFNESS L&W *(5°)	
			MD	CD	MD	CD
ISO 536	ISO 534	ISO 534	ISO 2493		DIN 53121	
<b>g/m<sup>2</sup></b>	<b>µm</b>	<b>cm<sup>3</sup>/g</b>	<b>mNm</b>	<b>mNm</b>	<b>mNm</b>	<b>mNm</b>
250	338	1.35	8.0	3.6	15.5	6.8
275	375	1.36	10.8	4.8	20.8	9.1
300	407	1.36	13.5	6.0	27.0	11.8
325	445	1.37	17.0	7.5	33.0	14.5
350	485	1.38	20.0	8.8	40.0	17.5
375	530	1.41	24.6	10.8	49.0	21.4
400	555	1.39	29.6	13.0	59.2	25.8
425	585	1.38	35.1	15.4	68.6	29.9
450	620	1.37	41.6	18.2	80.3	35.1
475	670	1.41	47.0	20.5	91.6	39.9

(\*) TABER VALUES ARE GUARANTEED. L&W FIGURES ARE CALCULATED.

<b>BRIGHTNESS</b>		
TOP	79.5%	ISO 2470-2

<b>TOLERANCES - SAMPLING ISO 186 (*)</b>	
SUBSTANCE	+/- 4%
CALIPER	+/- 5%
STIFFNESS	- 15%
BRIGHTNESS	+/- 1.5
TEST CONDITIONS	<b>T:</b> 23° C +/- 1 <span style="float: right;"><b>RH:</b> 50% +/- 2</span>

(\*) TOLERANCES BASED UPON 95% OF THE MEASURED VALUES.

**CERTIFICATIONS:** ISO 9001 / ISO 14001 / ISO 45001 / ISO 22000 / ISO 50001 / EMAS  
 FSC® - C127362 - CERTIFIED BOARD IS AVAILABLE ON REQUEST

To download the certificate, please click

